

**WHAT IS CLAIMED IS:**

1. An electronic camera comprising a camera device and a processor, wherein  
said camera device comprises a first generation means for generating a  
compressed image signal based on a photographed image signal, and a second generation  
5 means for generating a decompressed image signal based on the compressed image signal  
generated by said first generation means, and

said processor comprises a first activation means for activating said first  
generation means in response to a photographing instruction, a second activation means  
for activating said second generation means in response to completion of a generation  
10 process by said first generation means, and an output means for outputting to a monitor  
the decompressed image signal generated by said second generation means.

2. An electronic camera according to claim 1, wherein  
said processor further comprises a storage means for temporarily storing in a  
memory the compressed image signal generated by said first generation means, and a  
15 recording means for recording on a recording medium the compressed image signal  
stored in said memory in response to a recording instruction.

3. An electronic camera according to claim 1 or 2, wherein  
said first generation means includes a compression means for compressing said  
photographed image signal in a specific order; and

20 said camera device further comprises an image sensor in which a plurality of  
light-receiving elements for generating electric charges corresponding to an optical  
image of an object are formed, and a reading means for reading the electric charges  
generated by said plurality of light-receiving elements in an order correlating with said  
specific order.

4. An electronic camera according to claim 3, wherein

said compression means performs compression in units of a first pixel block; and  
said reading means performs reading in units of a second pixel block correlating  
with said first pixel blocks.

5. An electronic camera according to claim 4, wherein

5        said camera device further comprises a color filter arranged on a front surface of  
said image sensor and having a plurality of colors of color elements, and a color  
separation means for subjecting to color separation electric charge signals each of which  
has only color information of one of said plurality of colors, and

10        said second pixel block is larger than said first pixel block, and two second pixel  
blocks adjacent to each other are partly overlapping.

6. An electronic camera according to any one of claims 3 to 5, wherein  
said image sensor is a CMOS type.

7. An electronic camera according to any one of claims 3 to 6, wherein  
said second generation means includes a decompression means for subjecting said  
15        compressed image signal to a decompression process, and a resolution reduction means  
for reducing a resolution of the image signal decompressed by said decompression means  
to generate said decompressed image signal.

8. An electronic camera according to any one of claims 3 to 7, wherein  
said compression means performs compression in a lossy format.

20        9. An electronic camera according to any one of claims 1 to 8, wherein  
said photographed image signal is a still image signal.